

# List of Figures

---

|   | <u>Page</u> |
|---|-------------|
| Figure 1. Representative event tree illustrating the relationship between the frequency of train accident and conditional probabilities of subsequent events in the analysis.   | 11          |
| Figure 2. LNG DOT-113 train accident model overview.  | 12          |
| Figure 3. Frequency (count) of the first car position-in-train for mainline derailments with train speeds greater than 25 mph up to 50 mph (total count equals 3,501 derailments).  | 16          |
| Figure 4. Frequency (count) of the first car position-in-train for mainline derailments with train speeds less than or equal to 25 mph (total count equals 14,180 derailments).   | 17          |
| Figure 5. Flow chart describing the LNG LOC probability estimation approach.  | 21          |
| Figure 6. Block diagram for PHAST.  | 27          |
| Figure 7. PHAST Risk consequence event trees for a continuous release without liquid rainout; for example, applied to the 0.5-inch leak and 2-inch leak along mainline movement.  | 33          |
| Figure 8. PHAST Risk consequence event trees for an instantaneous release without liquid rainout; for example, applied to the catastrophic rupture along mainline movement.   | 34          |
| Figure 9. FN curves for the mainline train movement with train speeds up to 25 mph along different population densities (from 500 up to 20,000 people/mile <sup>2</sup> ) for one-mile section of the mainline. Note that these FN curves are only for a one-mile section of mainline with the corresponding population density.                      | 42          |
| Figure 10. FN curves for the mainline train movement with train speeds greater than 25 mph up to 50 mph along different population densities (from 500 up to 20,000 people/mile <sup>2</sup> ) for one-mile section of the mainline. Note that these FN curves are only for a one-mile section of mainline with the corresponding population density. | 44          |
| Figure 11. FN curve of the aggregate SR for the mainline train movement of LNG DOT-113s for the low speed case (up to to 25 mph) and high speed case (greater than 25 mph and up to 50 mph) along the example mainline route.   | 46          |