

Description	Unit Price	Qty	Ext. Price
<p>Standard 1U Heatsink</p> <p>Standard 1U Heatsink</p> <p>3200MT/s RDIMMs</p> <p>Performance Optimized</p> <p>Diskless Configuration (No RAID, No Controller)</p> <p>No Controller</p> <p>No Hard Drive</p> <p>BOSS controller card + with 2 M.2 Sticks 240G (RAID 1),LP</p> <p>No Operating System</p> <p>No Media Required</p> <p>iDRAC9,Enterprise</p> <p>iDRAC Group Manager, Enabled</p> <p>iDRAC,Legacy Password</p> <p>Riser Config 2, 3x16 LP</p> <p>Broadcom 57416 Dual Port 10GbE BASE-T & 5720 Dual Port 1GbE BASE-T, rNDC</p> <p>No Internal Optical Drive for x4 and x8 HDD Chassis</p> <p>8 Standard Fans for R640</p> <p>Dual, Hot-plug, Redundant Power Supply (1+1), 750W</p> <p>LCD Bezel</p> <p>Dell EMC Luggage Tag</p> <p>Quick Sync 2 (At-the-box mgmt)</p> <p>Performance BIOS Settings</p> <p>UEFI BIOS Boot Mode with GPT Partition</p> <p>ReadyRails Sliding Rails With Cable Management Arm</p> <p>No Systems Documentation, No OpenManage DVD Kit</p> <p>Dell Hardware Limited Warranty Plus On-Site Service</p> <p>ProSupport: Next Business Day On-Site Service After Problem Diagnosis, 5 Years</p> <p>ProSupport: 7x24 HW/SW Technical Support and Assistance, 5 Years</p> <p>Thank you choosing Dell ProSupport. For tech support, visit //www.dell.com/support or call 1-800- 945-3355</p> <p>On-Site Installation Declined</p> <p>(8) 32GB RDIMM, 3200MT/s, Dual Rank</p> <p>Broadcom 57416 Dual Port 10GbE BASE-T Adapter, PCIe Low Profile</p> <p>NVIDIA® Tesla™ T4 16GB Passive, Single Slot, Low Profile GPU</p> <p>(2) C13 to C14, PDU Style, 12 AMP, 6.5 Feet (2m) Power Cord, North America</p> <p>NASPO ValuePoint 17AHC C000000007982 WN08AGW TRP Seminole 26AHI C000000007806 53AHF</p>			

Continued On Next Page ...