

- Condition 6.4 requires repeated testing for those in Condition 6.3. As explained above, no repeated biofilter VOC testing and As/Cr VI testing is required.
- Condition 6.5 includes some additional requirements for the above testing, and requires that the facility keep records of some operating parameters during the tests.
- The recorded control device operating parameters will be used to establish the set points specified in Condition 6.8.
- Condition 6.6 requires that the facility record the tested results/emission factors from the testing required by Conditions 6.3 and 6.4.
- Condition 6.7 requires that the facility, in the event if any tested results are higher than the associated emission factors used in the application and included in Conditions 7.8 – 7.14, use the higher tested emission rate to track actual emissions and submit an application for updating the higher emission rates. The facility is also allowed to demonstrate that the emission factors derived are not representative of normal emissions in the application.

The following are the testing requirements for Phase II:

- Condition 6.9 contains all the initial performance tests in order to validate the uncontrolled NO_x and CO emission factors and after-control VOC, Total PM, and HAP emission factors. Condition 6.9 also includes the initial performance test to validate the 0 lb/ton As, and Cr VI emission factors. Note that the facility did not claim any CO control efficiency by the RTO.
- Note that VOC emissions from the biofilter are monitored with the VOC CEMS, so repeated VOC testing for the biofilter stack is not needed.
- The initial performance tests for As and Cr VI is needed to prove the facility's claim that burning virgin wood would not emit any As and Cr VI. No repeated test is needed if the initial test results are zero.

If the initial tests detect As and/or Cr VI, the facility will be required to submit an application that will either update the As or Cr VI emission factor in Section 7 or remove the MER caps by submitting a TIA. Whether repeated tests is needed will be determined during the review of that application.

- Condition 6.10 requires repeated testing for those in Condition 6.3. As explained above, no repeated biofilter VOC testing and As/Cr VI testing is required.
- Condition 6.11 includes some additional requirements for the above testing, and requires that the facility keep records of some operating parameters during the tests.
- The recorded control device operating parameters will be used to establish the set points specified in Condition 6.14.
- Condition 6.12 requires that the facility record the tested results/emission factors from the testing required by Conditions 6.9 and 6.10.