

**State of Georgia
Department of Natural Resources
Environmental Protection Division**

**Permit No.
2499-075-0028-E-01-0**

Page 34 of 43

The Permittee shall calculate NO_x emissions from the entire facility by using the following emission factor and the equation provided in this condition prior to initial performance tests. If any performance testing required in Conditions 6.9a.i. and 6.10 reveals emission factors higher than the emission factor listed below, the Permittee shall comply with Condition 6.13.

Table 7.18: NO_x Emission Factor That Should Be Used Before Any Test Results Are Available

Pollutant	Stack S1 (BIO Outlet)
	BUR5 and BUR6
NO _x	0.194 lb/MMBtu

The Permittee shall use the monthly records to calculate the facility-wide NO_x emissions during each calendar month. The Permittee shall notify the Division in writing if the facility-wide NO_x emissions exceed 20.75 tons during any calendar month. This notification shall be postmarked by the fifteenth day of the following month and shall include an explanation of how the Permittee intends to maintain compliance with the **NO_x** emission limitation in Condition 2.1.

7.19 Upon the initial startup of Phase II, the Permittee shall calculate and record the amount of CO emissions from the entire facility in each calendar month, using the following equation:
[391-3-1-.02(6)(b)1.]

$$ER_{CO} = (EF_{CO/S1} * H_B) / 2,000$$

Where:

- ER_{CO} = Monthly CO emission rate from the entire facility, in tons per month.
- EF_{CO/S1} = CO emission factor for Stack S1, in lbs CO/MMBtu.
- H_B = Monthly combined heat input into BUR5 and BUR6, combined, determined and recorded in accordance with Conditions 7.16d. and e.
- 2,000 = Conversion Factor to Convert Pound into Ton.

The Permittee shall calculate CO emissions from the entire facility by using the following emission factor and the equation provided in this condition prior to initial performance tests. If any performance testing required in Conditions 6.9b.i. and 6.10 reveals emission factors higher than the emission factor listed below, the Permittee shall comply with Condition 6.13.

Table 7.19: CO Emission Factor That Should Be Used Before Any Test Results Are Available

Pollutant	Stack S1 (BIO Outlet)
	BUR5 and BUR6
CO	0.194 lb/MMBtu