State of Georgia Department of Natural Resources Environmental Protection Division

Permit No. 2499-075-0028-E-01-0

Page 36 of 43

Table 7.20:	VOC	Emission	Factor	That	Should	Be	Used	Before	Any	Test	Results	Are
Available												

Pollutant	Stack S1	(RTO Outlet)	Stack S2 (BIO Outlet)				
	DRY5	& DRY6	DWS1 & DWS2 / DHM1 – DHM6 / PM1 – PM32 / COOL1 – COOL4				
	Factor Name	Factor and Unit	Factor Name	Factor and Unit			
VOC	EF _{VOC/DR}	6 lb/ton wood	EF _{VOC/S2}	0.233 lb / ton wood			
	DRE	98%					

The Permittee shall use the monthly records to calculate the facility-wide VOC emissions during each calendar month. The Permittee shall notify the Division in writing if the facility-wide VOC emissions exceed 20.75 tons during any calendar month. This notification shall be postmarked by the fifteenth day of the following month and shall include an explanation of how the Permittee intends to maintain compliance with the VOC emission limitation in Condition 2.1.

7.21 Upon the initial startup of Phase II, the Permittee shall calculate and record the amount of Total PM emissions from the entire facility in each calendar month, using the following equation: [391-3-1-.02(6)(b)1.]

 $ER_{PM} = [(EF_{PM/S1} * W_{DR}) + (EF_{PM/S2} * W_{COOL}) + (EF_{PM/S4} * T_{SST1}) + (EF_{PM/S5} * T_{SST2}) + (EF_{PM/S6} * T_{CYC})] / 2,000$

Where:

ER_{PM} = Monthly Total PM emission rate from the entire facility, in tons per month.

EF_{PM/S1} = Total PM emission factor for Stack S1, in lbs Total PM/ton wood.

 W_{DR} = Monthly throughput of Dryers DRY5 and DRY6, combined, determined and

recorded in accordance with Condition 7.16a.

EF_{PM/S2} = Total PM emission factor for Stack S2, in lbs Total PM/ton wood.

W_{COOL} = Monthly throughput of COOL1 - COOL4, combined, determined and

recorded in accordance with Condition 7.16b.

EF_{PM/S4} = Total PM emission factor for Stack S4, in lbs Total PM/hr.

 T_{SST1} = Monthly operating hours of SST1, determined and recorded in accordance

with Condition 7.17a.

EF_{PM/S5} = Total PM emission factor for Stack S5, in lbs Total PM/hr.

 T_{SST2} = Monthly operating hours of SST2, determined and recorded in accordance

with Condition 7.17b.

EF_{PM/S6} = Total PM emission factor for Stack S6, , in lbs Total PM/hr.

T_{CYC} = Monthly operating hours of the fuel dust silo, determined and recorded in

accordance with Condition 7.17c.

2,000 = Conversion Factor to Convert Pound into Ton.