

Figure 30.	Event tree for yard movement for train Configuration 1 (C-1). “Outcome Event Frequency” is the product of the “Initiating Event Frequency,” “Derailment Probability,” “Multiple ISO Accident Probability,” and “Release Probability.”	59
Figure 31.	Aerial view of the Hialeah Yard. The train route along the outside yard rail lines is red and a representative location of lifting operations is shown as a green dot.	65
Figure 32.	Aerial view of the Hialeah Yard. The train route through the yard is red and the range of lifting operations along the intermodal ramp is shown as a green line.	65
Figure 33.	Aerial view of Port of Miami. The yard rail line is red and the approximate location of lifting operations is represented as a green dot.	66
Figure 34.	Aerial view of the Port Everglades intermodal facility. The yard rail line is red and the approximate location of lifting operations is represented as a green dot.	67
Figure 35.	Aerial view of the Bowden Yard. The yard rail line is red and the approximate location of the lifting operations is represented as a green dot.	68
Figure 36.	Aerial view of the Hialeah Yard depicting the four consolidated census blocks used to represent nearby populations.	71
Figure 37.	Aerial view of the Port of Miami depicting the three distinct population densities.	73
Figure 38.	Aerial view of the Port Everglades intermodal facility depicting the four distinct population densities.	75
Figure 39.	Aerial view of the Bowden Yard depicting the five consolidated census blocks used to represent nearby populations.	77
Figure 40.	Average population density per latitudinal mile from the Bowden Yard to the Hialeah Yard.	79
Figure 41.	Aerial image of the route between Hialeah Yard and the Port of Miami.	80
Figure 42.	Representative graphical output of IR versus distance from PHAST Risk for slow train speed, train configuration C-1, and the highest population density of 11,800 people per square mile. The peak value is located at the route. The IR drops in a parabolic fashion moving perpendicularly away from the route.	85
Figure 43.	FN curve for the baseline train configuration C-1 mainline train movement for train speeds less than 25 mph along the highest population density portion of the mainline (at 11,800 people/mile ²).	86
Figure 44.	Representative graph of IR versus distance for high speed train, train configuration C-1, and a population density of 11,800 people per square	