

**State of Georgia
Department of Natural Resources
Environmental Protection Division**

Permit No. 2499-075-0028-E-01-1

Page 22 of 29

the Permittee intends to maintain compliance with the **NO_x** emission limitation in Condition 2.1.

7.19 Upon the initial startup of Phase II, the Permittee shall calculate and record the amount of CO emissions from the entire facility in each calendar month, using the following equation:
[391-3-1-.02(6)(b)1.]

$$ER_{CO} = [(EF_{CO/S1} * H_B) + (EF_{CO/BLR}) * (H_{BLR}) + (EF_{CO/SILO} * W_{SILO})] / 2,000$$

Where:

- ER_{CO} = Monthly CO emission rate from the entire facility, in tons per month.
- EF_{CO/S1} = CO emission factor for Stack S1, in lbs CO/MMBtu, determined in the most recent performance tests per Condition 6.12b. Before the initial performance test is conducted, the Permittee is allowed to use the CO emission factor in Table 7.19 below.
- H_B = Monthly combined heat input into BUR5 and BUR6, combined, determined and recorded in accordance with Conditions 7.16d. and e.
- EF_{CO/BLR} = U.S. EPA AP-42 CO emission factor for Boiler BLR, 84 lbs CO/MMcf NG).
- H_{BLR} = Monthly natural gas consumption by Boiler BLR, in MMcf NG/mo, determined and recorded in accordance with Condition 7.16g.
- EF_{CO/SILO} = CO emission factor for Finished Pellet Silos SILO1 – SILO16, in lbs CO/ton wood, determined in the most recent performance tests per Condition 6.12c. Before the initial performance test is conducted, the Permittee is allowed to use the CO emission factor in Table 7.19 below.
- W_{SILO} = Monthly throughput of SILO1 – SILO16, determined and recorded in accordance with Condition 7.16c.
- 2,000 = Conversion Factor to Convert Pound into Ton.

Table 7.19: CO Emission Factor That Should Be Used Before Any Test Results Are Available

Pollutant	Stack S1 (BIO Outlet)	No Stack ID
	BUR5 and BUR6	SILO1 – SILO16
CO	0.194 lb/MMBtu	0 lb/ton wood output

The Permittee shall use the monthly records to calculate the facility-wide CO emissions during each calendar month. The Permittee shall notify the Division in writing if the facility-wide CO emissions exceed 20.75 tons during any calendar month. This notification shall be postmarked by the fifteenth day of the following month and shall include an explanation of how the Permittee intends to maintain compliance with the CO emission limitation in Condition 2.1.

7.20 Upon the initial startup of Phase II, the Permittee shall calculate and record the amount of VOC emissions from the entire facility in each calendar month, using the following equation:
[391-3-1-.02(6)(b)1.]