

### Surficial Aquifer Drawdown - 1 ft from well pumping 1,000 gpm - Maximum Drawdown Case

$s_1 = (Q_2/2\pi(T_1 + T_2))(\ln(r_e/r) - K_0(\beta) - K_0(\beta\epsilon)I_0(\beta)/I_0(\beta\epsilon))$			Upper Floridan Aquifer	$Q_2/2\pi(T_1 + T_2)$	Surficial Aquifer	Floridan Aquifer
Parameter	Value	Units	Pumping ( $Q_2$ in gpm)	(ft)	Drawdown ( $s_1$ in feet)	Drawdown ( $s_2$ in feet)
Time since beginning of pumping (t)	4.0	years	1000	2.45115841	2.65E-01	29.78
Radial distance from Lower Floridan aquifer pumping well (r)	1	feet				
Transmissivity of surficial aquifer ( $T_1$ )	1,500	ft <sup>2</sup> /day				
Specific Yield of surficial aquifer ( $S_1$ )	0.30000					
Transmissivity of Upper Floridan aquifer ( $T_2$ )	11,000	ft <sup>2</sup> /day				
Storativity of Upper Floridan aquifer ( $S_2$ )	0.000005					
Hydraulic conductivity of confining unit ( $K'$ )	1.00E-04	ft/day				
Thickness of confining unit (b')	325	feet				
$v_1 = T_1/S_1$	5,000	ft <sup>2</sup> /day				
$v_2 = T_2/S_2$	2,200,000,000	ft <sup>2</sup> /day				
$v_v = 2v_1v_2/(v_1 + v_2)$	10,000	ft <sup>2</sup> /day				
$r_e = 1.5(v_v t)^{1/2}$ not used, chosen to be 44,608 ft	44,608	feet				
$B_1 = (T_1/(K'/b'))^{1/2}$	69,821	feet				
$B_2 = (T_2/(K'/b'))^{1/2}$	189,077	feet				
$\beta_1 = r/B_1$	0.00001432					
$\beta_2 = r/B_2$	0.00000529					
$\beta^2 = \beta_1^2 + \beta_2^2$	0.00000000					
$\beta$	0.00001527					
$\beta\epsilon_1 = re/B_1$	0.63888905					
$\beta\epsilon_2 = re/B_2$	0.23592542					
$\beta\epsilon^2 = \beta\epsilon_1^2 + \beta\epsilon_2^2$	0.46384001					
$\beta\epsilon$	0.68105801					
$\ln(r_e/r)$	10.706					
$K_0(\beta)$	11.206					
$K_0(\beta\epsilon)$	0.680809207					
$I_0(\beta\epsilon)$	1.119365277					
$I_0(\beta)$	1					
$\delta 1 = T_1/T_2$	0.136363636					