

State of Georgia
Department of Natural Resources
Environmental Protection Division

Page 14 of 43

Permit No.
2499-075-0028-E-01-0

- ii. Sizing/Screening/Transport 1 (ID No. SST1)

Test at Baghouse BGH4 outlet (Stack ID No. S3). The test results shall be recorded in pounds per hour (lbs/hr).
 - iii. Sizing/Screening/Transport 2 (ID No. SST2)

Test at Baghouse BGH5 outlet (Stack ID No. S4). The test results shall be recorded in lbs/hr.
 - iv. The fuel dust silo

Test at Cyclone CYC outlet (Stack ID No. S5). The test results shall be recorded in lbs/hr.
 - e. Hazardous Air Pollutants (Acetaldehyde, Acrolein, Formaldehyde, Hydrogen chloride, Methanol, Phenol, Propionaldehyde; and Other HAPs)
 - i. The dryers (ID Nos. DRY1 – DRY4), dry wood silos (ID Nos. DWS1 and DWS2), dry hammermills (ID Nos. DHM1 and DHM2), pellet mills (ID Nos. PM1 – PM16), and pellet coolers (ID Nos. COOL1 and COOL2)

Test at the biofilter (ID No. BIO) outlet (Stack ID No. S1). The test results shall be recorded in pounds HAP per ton wood processed by COOL1 and COOL2, combined.
 - ii. Finished Pellet Silos 1-8 (ID Nos. SILO1 – SILO8)

Choose one of the silos that just received fresh pellets and test its stack. The test results shall be recorded in pounds HAP per ton wood loaded into the silo.
 - f. Arsenic (As) and Hexavalent Chromium (Cr VI)
 - i. The burners (ID Nos. BUR1 – BUR4)

Test at the biofilter (ID No. BIO) outlet (Stack ID No. S1). The test results shall be recorded in pounds As or Cr VI per ton wood processed by DRY1 – DRY4, combined.
- 6.4 The Permittee shall repeat the performance tests specified in Condition 6.3, except Conditions 6.3c.i. and 6.3f.i., according to the following schedule:
[391-3-1-.02(6)(b)1.(i)]
- a. Subsequent performance tests shall be conducted no more than 37 months after the previous performance test.